

MOISTURE & HUMIDITY CONTROL SPECIALIST DEHUMIDIFIER MDH-30B



CONTROL INDOOR HUMIDITY WITH DEHUMIDIFIER

Control of indoor humidity is important for health and comfort because high humidity can cause condensation, leading to potential material degradation and biological contamination such as MOLD. High humidity also supports dust mite populations, which contribute to allergies.

Fungi and bacteria are normally present on most interior surface in building. These microorganisms become problematic to IAQ when they amplify or grow on surface, sometimes to the point where the growth is visibly obvious.

- Environmentally Friendly Refrigerant
- Newly manufactured refrigerant
- Non Ozone Depleting
- High efficient (better at absorbing and releasing heat)
- RH stay over 65% for prolonged periods of times mold is likely to grow
- Optimum humidity level in a room is between 50% - 60%

SPECIAL FEATURES

Rotary compressor with Environmental Friendly Refrigerant R134A

Electronic Control

LED display with touch-key

Up to 24 hours timer

Water full alarm and auto shut off

Optional continuous drainage



A Smart Air Quality Solutions

TECHNICAL SPECIFICATIONS

Dehumidifying capacity 30°C, 80% RH	30L/Day
Full Tank Capacity	6.0L
Power Consumption (Max)	240W
Maximum Current	1.15A
Dimension (WxDxH) mm	402 × 260 × 610 mm
Weight	15.8kg
Warranty	2 years
Power Supply	230V/1Ph/50Hz

KUALA LUMPUR No 6, Jalan 3/91A, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur.

Tel: 603 - 9202 7295 Email: enquiry@aaq.com.my

PENANG 405K, Jalan Perak, 11600 Georgetown, Pulau Pinang

JOHOR No. 20 & 20-01, Jalan Setia 4/11, Taman Setia Indah 81100, Johor Bahru, Johor.

Tel : + (6) 012- 378 3295 Email : enquiry@aaq.com.my Tel: + (6) 012- 397 3295 Email: enquiry@aaq.com.my